

TAWA-T1040 Pico-ITX IPC RACKMOUNT

Feature:


- 1. 1U rackmount server chassis with four VIA P720 or P820 Pico-ITX systems. (Can be custom design for all brand Pico-ITX board)
- 2. Easy system integration.
- 3. Both internal and external withdrawable storage capacities.
- 4. Support up to 4 Serial ATAII drives trays.




Specifications:

Front Panel	 Power switch x 4 sets. Power LED x 4 sets. HDD LED x 4 sets. (USB Port x 2) x 4 sets.
Back Panel	 VGA Port x 4 sets. (USB Port x 2) x 4 sets. LAN Port x 4 sets. DC Jack x 4 sets. HDMI Port x 4 sets.
Internal Structure	 4cm system cooling x 2. Compact flash module x 4 sets (not included) or 2.5" SATA HDD x 4 sets. (HDD brackets not included)
Dimension (WxDxH)	18.98 x 12.52 x 1.73 inch (482.0 x 318.0 x 43.9 mm)
Material	Heavy dust cold-rolled steel.
Surface	Black wet paint with texture coat.
Colour	Black. Customizable colour.







Power Solutions:

Internal Power Supply	External AC adapter
On Motherboard	60 Watts (12V)

UNIT:mm

E-mail: sales@kiwatek.com Website: www.kiwatek.com